

Introduction

EQUITONE [natura] and [natura] Pro have semi transparent coatings. The cut edges and fixing holes of these panels need a treatment with an impregnating transparent agent Luko.



Product characteristics

Delivery form ready for use
View milky liquid

Luko tools

LUKO paint tray for 0,5 L + applicator with special microfiber cloth (5 x 8 cm).

Instructions for use



Shake well before use and shake regularly while using (demixing can appear).

Soak the applicator in the impregnating agent.

The LUKO impregnating agent is used undiluted.

Wipe the applicator on the surface of the paint tray to prevent dripping.

The temperature for application is between 5 and 25 °C.

The minimum ambient temperature for application of Luko should be 5 °C.

However, for temperatures above 25 °C, the Luko tend to dry prematurely and extra coats are highly recommended to fully cover the panel edges.

Apply LUKO only in a dry environment.

Finishing must be done sheet by sheet and NOT a stack all at once.

During application the applicator must be held slightly at an angle to prevent the liquid running on the visible side.

Surplus LUKO impregnating agent must be immediately removed with a clean cloth to prevent soiling or staining the panel finish.

Do NOT reuse a cloth containing LUKO residue unless it is thoroughly cleaned to prevent staining and streak marks on the panel surface.

Do NOT pour the LUKO impregnating agent left in the paint tray back into the pot or use later.

The complete impregnation of the cut edges of the façade panels prevents moisture absorption along the edges and any resulting temporary dark discoloration of the visible surfaces around the edges.

The LUKO impregnating agent must FULLY cover the saw cuts.



Consumption

0,5 L per 500 meter cut edge

Packaging

Applicator set Art.N° 4012104
Pot 0.5 L Art. N° 23287
Pot 1 L Art. N° 23288
Bucket 10 L Art. N° 23289

Storage

Shelf life : 6 months after filling date

Disclaimer

The information in this Material Information Sheet is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please contact your local EQUITONE Sales Organization to ensure you have the most current version.

All information contained in this document is copyrighted ©.

All figures contained in this document are illustrations and should not be used as construction drawings.

This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use